



★ VDS Specifications

Model (Cascade Refresh)	VDS-5050	VDS-6550	VDS-7550	VDS-8050	VDS-R-G530	VDS-R-G63
Dimension	800 (L) x 448 (W) x 90 (H) mm	800 (L) x 448 (W) x 90 (H) mm	800 (L) x 448 (W) x 90 (H) mm	800 (L) x 448 (W) x 90 (H) mm	800 (L) x 448 (W) x 90 (H) mm	800 (L) x 448 (W) x 90 (H) mm
CPU	2*Intel® Xeon® Processor Silver 4210R 10c 2.4GHz	2*Intel® Xeon® Processor Silver 4214R 12c 2.4GHz	2*Intel® Xeon® Processor Gold 6226R 16c 2.9GHz	2 * Intel® Xeon® GOLD 6248R 24C 3.0 GHz	2*Intel® Xeon® Processor Gold 6226R 16c 2.9GHz	2*Intel® Xeon® Processor Gold 6244 8c 3.6GHz
Memory Type	DDR4	DDR4	DDR4	DDR4	DDR4	DDR4
Memory	128G (4*32G)	192G (6*32G)	256G (8*32G)	256G (8*32G)	128G (4*32G)	128G (4*32G)
Memory Slots	24 slots, max support 32G per slot	24 slots, max support 32G per slot	24 slots, max support 32G per slot	24, max support 64G per slot	24 slots, max support 32G per slot	24 slots, max support 32G per slot
	System Disk 2*240G				System Disk 1*240G	
Hard Drive	2 options available: 1. Intel 480G 2. Intel 960G (Minimum ONE disk, prohibit to deliver the server WITHOUT caching disk.)	2 options available: 1. Intel 480G 2. Intel 960G (Minimum ONE disk, prohibit to deliver the server WITHOUT caching disk.)	2 options available: 1. Intel 480G 2. Intel 960G (Minimum ONE disk, prohibit to deliver the server WITHOUT caching disk.)	2 options available: 1. Intel 480G 2. Intel 960G (Minimum ONE disk, prohibit to deliver the server WITHOUT caching disk.)	4 options available: 1. Intel 240G 2. Intel 480G 3. Intel 960G 4. Intel 1.92T (Minimum TWO disk, prohibit to deliver the server WITHOUT caching disk.)	4 options available: 1. Intel 240G 2. Intel 480G 3. Intel 960G 4. Intel 1.92T (Minimum TWO disk, prohibit to deliver the server WITHOUT caching disk.)
	Data disk is optional (quantity is minimum 2, and recommended as even number)					
Disk Slots	12 * front 2.5/3.5"	12 * front 2.5/3.5"	12 * front 2.5/3.5"	12 * front 2.5/3.5"	8 * front 2.5/3.5"	8 * front 2.5/3.5"
Max. storage capacity in single disk slot for data disk	8T					
NIC	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports
PCIe Type	PCIe 3.0	PCIe 3.0	PCIe 3.0	PCIe 3.0	PCIe 3.0	PCIe 3.0
Totle PCIe Slot	5	5	5	5	6	6
Spare PCIe Slot	1	1	1	1	3	3
Supported Network Card	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)
GPU	Not Support				Option: Light load: M10 Moderate or heavy load: T4, RTX6000, RTX8000 Max GPU quantity: TWO	Option: Light load: M10 Moderate or heavy load: T4, RTX6000, RTX8000 Max GPU quantity: TWO
IO Port	2*USB2.0 2*USB3.0 1*VGA	2*USB2.0 2*USB3.0 1*VGA	2*USB2.0 2*USB3.0 1*VGA	2*USB2.0 2*USB3.0 1*VGA	2*USB2.0 4*USB3.0 1*VGA	2*USB2.0 4*USB3.0 1*VGA
Serial Port	1					
PSU	800W or 900W dual PSU	800W or 900W dual PSU	800W or 900W dual PSU	900W or 1300W dual PSU	1200W dual PSU	1200W dual PSU



★ VDC Specifications

Model	VDC-2500	VDC-2600	VDC-4600	VDC-8500
Memory	4GB	4GB	8GB	8GB
Storage Capacity	64GB SSD	64GB SSD	64GB SSD	64GB SSD
Operating temperature	0-45 °C	0-45 °C	0-45 °C	0-45 °C
PSU	40W (Max)	40W (Max)	60W (Max)	150W (Max)
Power Supply Redundancy	N	N	Y	Y
GE Electrical Ports	6	6	6	4
GE Optical Port SFP	/	/	4	4
100GE Optical Port SFP+	/	/	/	2
Serial Port (RJ45)	1			
USB Port	2			
Dimension	375 (L) * 430 (W) * 44.5 (H) mm	375 (L) * 430 (W) * 44.5 (H) mm	400 (L) * 430 (W) * 44.5 (H) mm	600 (L) * 440 (W) * 89 (H) mm
Net Weight	3.85KG	3.85KG	4.5KG	12.95KG



★ Thin-Client Specifications

Model	Hardware Specification	Port	Dimensions (mm)	Power (w)	Weight (kg)	Scenario
STD-500	Intel x86 CPU, 2*cores 2.41GHz, 2G memory, 8G storage, USB*6 (2*USB 3.0), 1GE port*1, Dual Audio port*1	1*VGA + 1*HDMI	170 * 110 * 31	15	0.52	1. 3D Enterprise Design 2. 2D Desktop Dual Screen 3. 3D Desktop Dual Screen
STD-200H-S (VGA)	ARM A9 CPU, 4*cores 1.6GHz, 1G memory, 4G storage, USB*6, Dual Audio port*1, 100M Ethernet port*1	1*VGA	170 * 105 * 29	7	0.35	1. General Office 2. Education Scenario 3. Manufacturing 4. Call Center
STD-200H-S (HDMI)	ARM A9 CPU, 4*cores 1.6GHz, 1G memory, 4G storage, USB*6, Dual Audio port*1, 100M Ethernet port*1	1*HDMI	170 * 105 * 29	7	0.35	